KONKA

F Series
Floor Poster LCD

Economical Floor Standing





Programing

Visible program, free combination



Program Play

Support insert, set time



Terminal Management

Support grouping, authorize, revising, monitoring



System Management

Support remote auto update, checking on line, record User's data



Decode type

Audio support: Mp3. WMA, WAV and etc. **Image support:** JPG, BMP, TIFF and etc. **Video support:** H.264, FLV, Mp4, RMVB, MEPG2 and etc.



Others

Support pause and resume, auto switch, watch dog restart, two languages Chinese & English

Precise positioning
Professional and reliable

■ Clear - target: Precuse Advertising

■ Stable and reliable: Commercial A + screen, support 7x24 display

■ Cluster management: Single data base supports 3000pcs machine at the same time



Airport



Building-selling centre



PARAMETERS

	Size	32"-55"	65"-84"
LCD Panel	Resolution	1920x1080	3840x2160
	Type	60Hz LED BLU	
	Screen ratio	16:9	
	Response time	8ms	
	Brightness	≤350 cd/m2	
	Contrast ratio	≤1200:1	
	Life span	≤50000 (hours)	
	Viewing angle	H178° / V178°	
Android configuration	CPU	HD decoding chip (4 cores 1.8GHz)	
	RAM/Memory	2G	
	Built-in storage Volume	EMMC 16G Extendible SD slot *1	
Windows configuration	CPU	Inter 1.8-3.6GHz (Optional)	
	Memory	4G	
	Hard disk store volume	500G / 128SSD	
Interface	Networks	WIFI, Rj45, 3G/4G (Optional)	
	IO interface	2 USB interface / 4 USB socket (Optional)	
	Video output	VGA*1, HDMI*1	
	Speaker	8Ω5W*2	
Working environment	Working temperature	-10°C ~ 46°C	
	Working humidity	10~80%	
	Power input	AC 100 - 240V ~ (+/-10%) 50/60Hz	
	Max power	110W	
	Standby power	< 0.9W	

KONKA



PT. CREATIVE MEDIA INDONESIA
A-21 Rukan Sentra Bisnis Pluit
Jl. Pluit Sakti no. 28 Jakarta 14450 Indonesia
Phone : +6221 666 75 020

www.cmi-led.com cmi led